CLAIMS

What is claimed is:

	,	Λ
the track of the track that there is the track	4 mb	1. A system-on-a-chip integrated circuit structure comprising:
	2 Cull	a bridge having a plurality of charnels;
	3	a processor local bus connected to said bridge, wherein said bridge
	4	includes a first channel dedicated to said processor local bus;
	5	at least one logic device connected to said processor local bus;
	6	a peripheral device bus connected to said bridge, wherein said bridge
	7	includes a second channel dedicated to said peripheral device bus;
	8	at least one peripheral device connected to said peripheral device bus;
	9	at least one memory unit connected to said bridge, wherein said bridge
	10	includes a third channel dedicated to said memory unit; and
	11	at least one input/output unit connected to said bridge, wherein said bridge
	12	includes a fourth channel dedicated to said input/output unit.
	1	2. The structure in claim 1, wherein each of said channels includes buffer
	2	memories adapted to store data when a previous data transfer is being performed.

2

5

1

2

3

1 3. The structure in claim 2, wherein said buffer memories comprise first-in first-out buffer memories.

2

3

- 4. The structure in claim 1, wherein each of said channels includes a multiport static random access memory (SRAM) adapted to store data when a previous data transfer is being performed.
- 5. The structure in claim 1, wherein each of said channels includes a multiplexor adapted to selectively connect to other channels.
 - 6. The structure in claim 1, wherein said at least one memory unit comprises a first-type memory unit and a second-type memory unit different than said first-type memory unit, wherein said third channel is dedicated to said first-type memory unit and said bridge includes a fifth channel dedicated to said second-type memory unit.
 - 7. The structure in claim 6, wherein said first-type memory unit comprises static random access memory (SRAM) and said second-type memory unit comprises synchronous dynamic random access memory (SDRAM).



- 8. The structure in claim 1, wherein said at least one input/output unit comprises one or more of a peripheral interface, graphics interface, and serial bus interface, and wherein said bridge includes dedicated channels for each of said peripheral interface, graphics interface, and serial bus interface.
- 9. The structure in claim 1, wherein said at least one peripheral device includes one or more of a serial connection, network interface connection, and programmable input/output connection each connected to said peripheral device bus.
- 10. A system-on-a-chip integrated circuit structure comprising:

 a bridge having a plurality of channels;

 at least one bus connected to a unique dedicated channel in said bridge;

 at least one memory unit connected to a unique dedicated channel in said

 bridge; and

 at least one input/output unit connected to a unique dedicated channel in
- 11. The structure in claim 10, wherein said at least one bus includes:
 a processor local bus connected to said bridge, wherein said bridge

includes a first channel dedicated to said processor local bus; and

said bridge.

2

3

5 Contid

a peripheral device bus connected to said bridge, wherein said bridge includes a second channel dedicated to said peripheral device bus,

wherein said structure further comprises:

at least one logic device connected to said processor local bus; and at least one peripheral device connected to said peripheral device bus.

- 1 12. The structure in claim 10, wherein each of said channels includes buffer 2 memories adapted to store data when a previous data transfer is being performed.
- 1 13. The structure in claim 12, wherein said buffer memories comprise first-in 2 first-out buffer memories.
 - 14. The structure in claim 10, wherein each of said channels includes a multiport static random access memory (SRAM) adapted to store data when a previous data transfer is being performed.
- 1 15. The structure in claim 10, wherein each of said channels includes a multiplexor adapted to selectively connect to other channels.
- 1 16. The structure in claim 10, wherein said at least one memory unit
 2 comprises a first-type memory unit and a second-type memory unit different than

3	said first-type memory unit, wherein said bridge includes a first channel is			
4	dedicated to said first-type memory unit and a second channel dedicated to said			
	second-type memory unit.			
1 CONTA	17. The structure in claim 16, wherein said first-type memory unit comprises			
2	static random access memory (SRAM) and said second-type memory unit			
3	comprises synchronous dynamic random access memory (SDRAM).			
1	18. The structure in claim 10, wherein said at least one input/output unit			
2	comprises one or more of a peripheral interface, graphics interface, and serial bus			
3	interface, and wherein said bridge includes unique dedicated channels for each of			
4	said peripheral interface, graphics interface, and serial bus interface.			
1	19. The structure in claim 11, wherein said at least one peripheral device			
2	includes one or more of a serial connection, network interface connection, and			
3	programmable input/output connection each connected to said peripheral device			
4	bus.			
1	20. A bridge for a system-on-a-chip (SoC) integrated circuit structure			
2	comprising:			
3	a plurality of dedicated channels each uniquely connected to one or more			

4	01:	
5		at least one bus within said SoC;
$\left\{ \left\{ \right\} \right\}$		at least one memory unit within said SoC;
7cmtd.		at least one input/output unit within said SoC; and
8		at least one peripheral device within said SoC.
1	21.	The structure in claim 20, wherein said at least one bus includes:
2		a processor local bus connected to said bridge, wherein said bridge
3	includ	es a first channel dedicated to said processor local bus; and
4		a peripheral device bus connected to said bridge, wherein said bridge
5	includ	les a second channel dedicated to said peripheral device bus,
6		wherein said SoC includes:
7		at least one logic device connected to said processor local bus; and
8		at least one peripheral device connected to said peripheral device bus.
1	22.	The structure in claim 20, wherein each of said channels includes buffer
2	memo	ories adapted to store data when a previous data transfer is being performed.
1	23.	The structure in claim 22, wherein said buffer memories comprise first-in
2	first-o	out buffer memories.



- 24. The structure in claim 20, wherein each of said channels includes a multiport static random access memory (SRAM) adapted to store data when a previous data transfer is being performed.
- The structure in claim 20, wherein each of said channels includes a multiplexor adapted to selectively connect to other channels.
 - 26. The structure in claim 20, wherein said at least one memory unit comprises a first-type memory unit and a second-type memory unit different than said first-type memory unit, wherein said bridge includes a first channel is dedicated to said first-type memory unit and a second channel dedicated to said second-type memory unit.
 - 27. The structure in claim 26, wherein said first-type memory unit comprises static random access memory (SRAM) and said second-type memory unit comprises synchronous dynamic random access memory (SDRAM).
 - 28. The structure in claim 20, wherein said at least one input/output unit comprises one or more of a peripheral interface, graphics interface, and serial bus interface, and wherein said bridge includes unique dedicated channels for each of said peripheral interface, graphics interface, and serial bus interface.



29. The structure in claim 21, wherein said at least one peripheral device includes one or more of a serial connection, network interface connection, and programmable input/output connection each connected to said peripheral device bus.

4